


# MATERIAL SAFETY DATA SHEET

## SECTION 1 - MANUFACTURER INFORMATION

MANUF / DIST: CCS DISTRIBUTING INC  
1021 STARR AVE  
EAU CLAIRE, WI 54703  
PREPARER/CONTACT: GARY SOLEY  
EMERGENCY PHONE: 715-834-7080

TRADE NAME / SYNONYMS... : SATIN SHINE  
CHEMICAL NAME / SYNONYMS: NOT APPLICABLE  
CHEMICAL FAMILY..... : NOT APPLICABLE  
FORMULA..... : Proprietary  
PRODUCT CODE..... : NOT APPLICABLE

### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:



## SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (i)-(13)  
CHEMICAL / COMMON NAME CAS# PERCENTAGE PEL-OSHA TLV-ACGIH  
Mineral Spirits 8052-41-3 >1 100PPM 100PPM

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

## SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

\*Acute\*:

- Eyes - Can cause severe irritation, redness, tearing, blurred vision.
- Skin - Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

# MATERIAL SAFETY DATA SHEET

- c) Inhalation - Mild irritation.
- d) Ingestion - Can cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

\*Chronic\*

- a) Inhalation may increase susceptibility to respiratory illness.

## PRIMARY ROUTES OF ENTRY:

- a) Skin
- b) Inhalation

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

## EMERGENCY FIRST AID PROCEDURES:

- a) Skin - Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
- b) Eyes - Flush immediately with large quantities of running water for at least 15 minutes. Consult Physician.
- c) Inhalation - If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion - Do not induce vomiting. call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

## SECTION 4 - CHEMICAL DATA

BOILING POINT (F) . . . . . : >240	SPECIFIC GRAVITY (WATER=1) . . . . . : 0.795
VAPOR PRESSURE (mmHg) : 2	PERCENT VOLATILE BY VOLUME (%) . . . : >85.00
VAPOR DENSITY (AIR=1) : 4.9	EVAPORATION RATE (WATER=1) . . . . . : 24

SOLUBILITY IN WATER: Insoluble

APPEARANCE AND ODOR INFORMATION: Thin green liquid with a specific odor.

## SECTION 5 - FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 108° F T.C.C FLAMMABLE LIMITS: LEL= 0.9% UEL=6%

EXTINGUISHING MEDIA: Regular foam, waterfog, carbon dioxide or dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES:

# MATERIAL SAFETY DATA SHEET

a) Clear fire area of unprotected personnel. Do not enter confined fire area without full bunker gear, including a positive pressure mode breathing apparatus. Cool fire exposed containers with waterfog.

## UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights and other flames in locations distant from the material handling point. \*See additional comments.

## INCOMPATIBILITY ( Material To Avoid ):

Avoid contact with strong oxidizing agents such as chlorine, permanganate, etc.

## HAZARDOUS DECOMPOSITION PRODUCTS:

Burning may produce oxides of carbon and traces of hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

THIS PRODUCT IS STABLE.

## SECTION 6 - SPILL OR LEAK PROCEDURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Absorb on suitable absorbant and shovel into containers.

### WASTE DISPOSAL METHODS:

Contaminated absorbant may be disposed of according to local, state and federal regulations for products containing petroleum distillates.

## SECTION 7 - EXPOSURE CONTROL INFORMATION

### VENTILATION:

LOCAL EXHAUST: Below TLV(s)      MECHANICAL (General) : Explosion Proof

SPECIAL .....: N/A                      OTHER .....: N/A

### RESPIRATORY PROTECTION:

An appropriate NIOSH hydrocarbon canister or respirator for organic is advised of proper environmental control.

### PROTECTIVE GLOVES:

Wear - resistant gloves such as nitrile rubber, PVC, etc.

### OTHER PROTECTIVE EQUIPMENT:

a) To prevent repeated and prolonged skin contact, wear impervious clothing and

# MATERIAL SAFETY DATA SHEET

boots.

- b) Eye wash and quick drench facilities.

OTHER ENGINEERING CONTROLS: None Known

## WORK PRACTICES:

Eye wash fountain and safety shower should be accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

## HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

## SECTION 8 - SPECIAL PRECAUTIONS

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Keep away from heat, sparks and open flames.
- b) Do not store under freezing conditions or above 120 degrees F.
- c) Protect from physical damage and keep tightly closed.
- d) Do not store near acids or acidic materials and oxidizers.
- e) Containers mark NA1993

### MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

### OTHER PRECAUTIONS:

- a) containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.
- b) Always ground metal containers while pouring.

### OTHER ADDITIONAL COMMENTS:

\* Unusual Fire and Explosion Hazards

- a) Never use welding or a cutting torch on or near container (even empty) because product (even just residue) can ignite explosively.
- b) All 5 gallon pails and larger metal containers should be grounded when material is transferred.

SHIPPING INFO, UN/NA #'s, Secondary container label INFO NECESSARY OR SUGGESTED:

**COMBUSTIBLE LIQUID, n.o.s., NA1993, PG III, NO LABELS REQUIRED**

**KEEP OUT OF THE REACH OF CHILDREN!**