


MATERIAL SAFETY DATA SHEET

SECTION 1 - MANUFACTURER INFORMATION

MANUF / DIST: CCS DISTRIBUTING INC
1021 STARR AVE
EAU CLAIRE, WI 54703
PREPARER/CONTACT: GARY SOLEY
EMERGENCY PHONE: 715-834-7080
Emergency 24 hour Medical Chemical INFOTRAC 800-535-5053
TRADE NAME / SYNONYMS... : UNIVERSAL SOLVENT
CHEMICAL NAME / SYNONYMS: NOT APPLICABLE
CHEMICAL FAMILY..... : NOT APPLICABLE
FORMULA..... : Proprietary
PRODUCT CODE..... : NOT APPLICABLE

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:



SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (i)-(13)
CHEMICAL / COMMON NAME CAS# PERCENTAGE PEL-OSHA TLV-ACGIH
PETROLEUM DISTILLATE 64742-47-8 >1 100PPM 100PPM

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

Acute:

- Eyes - Can cause severe irritation, redness, tearing, blurred vision.
- Skin - Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

MATERIAL SAFETY DATA SHEET

- c) Inhalation - Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.
- d) Ingestion - Can cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

Chronic

- a) Inhalation may cause susceptibility to respiratory illness.

PRIMARY ROUTES OF ENTRY:

- a) Skin
- b) Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

EMERGENCY FIRST AID PROCEDURES:

- a) Skin - Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
- b) Eyes - In case of contact, immediately flush eyes with plenty of water. If irritation persists, seek medical help.
- c) Inhalation - If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion - Do not induce vomiting. call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F)	>392	SPECIFIC GRAVITY (WATER=1)	>0.780
VAPOR PRESSURE (mmHg) :	3	PERCENT VOLATILE BY VOLUME (%) . . .	>90.00
VAPOR DENSITY (AIR=1) :	N/A	EVAPORATION RATE (WATER=1)	24
SOLUBILITY IN WATER:	Insoluble in water. WGT. 6.6#/GAL		

APPEARANCE AND ODOR INFORMATION: Colorless liquid with petroleum odor.

SECTION 5 - FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 143°F T.C.C **FLAMMABLE LIMITS:** LEL=1.4% UEL= 9.3

MATERIAL SAFETY DATA SHEET

EXTINGUISHING MEDIA: Regular foam, waterfog, carbon dioxide or dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES:

Clear fire area of unprotected personal. Do not enter confined fire area without full bunker gear, including a positive pressure mode breathing apparatus. Cool fire exposed containers with waterfog.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

* See additional Comments SECTION*

INCOMPATIBILITY (Material To Avoid):

Avoid contact with strong oxidizing agents such as chlorine, permanganate, etc.

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning may produce oxides of carbon and traces of hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Absorb on suitable absorbant and shovel into containers.

WASTE DISPOSAL METHODS:

Contaminated absorbant may be disposed of according to local, state and federal regulations for products containing petroleum distillates.

SECTION 7 - EXPOSURE CONTROL INFORMATION

VENTILATION:

LOCAL EXHAUST: Below TLV(s)	MECHANICAL (GENERAL): EXPLOSION PROOF
SPECIAL : N/A	OTHER : N/A

RESPIRATORY PROTECTION:

An appropriate NIOSH approved hydrocarbon canister or respirator for organic vapor should be worn if needed.

PROTECTIVE GLOVES:

Wear - resistant gloves such as nitrile rubber, PVC, etc.

MATERIAL SAFETY DATA SHEET

OTHER PROTECTIVE EQUIPMENT: N/A

OTHER ENGINEERING CONTROLS: Eye wash and quick drench facilities.

WORK PRACTICES:

Eye wash fountain and safety shower should be accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 8 - SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) FLAMMABLE Keep away from heat, sparks and open flames.
- b) Protect from physical damage and keep tightly closed.
- c) Do not store under freezing conditions or above 120 degrees F.
- d) Do not store near acids or acidic materials and oxidizers.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

OTHER PRECAUTIONS:

- a) containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

OTHER ADDITIONAL COMMENTS:

* Unusual Fire* - Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights or other flames and ignition sources at an location distant from the material handling point. Never use a welding or cutting torch on or near container (even an empty one!) because product (even just residue) can ignite explosively. All 5 gallon pails and larger metal containers should be grounded when material is being transferred.

SHIPPING INFO, UN/NA #'s, Secondary container label INFO NECESSARY OR SUGGESTED:

COMBUSTIBLE LIQUID UN 1268. PG GP III NO LABELS SPECIFIED IN CFR's

KEEP OUT OF THE REACH OF CHILDREN!